

# TW THRU-WALL FLASHING

## SELF-ADHERING SHEET MEMBRANE

## PRODUCT DATA

### DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at [tamko.com](http://tamko.com) or call us at 800-641-4691.

**TW-THRU WALL FLASHING** is a self-adhering SBS modified bitumen flashing membrane with a polymer surface film.

- Treated release film for ease of installation
- Available in factory precut widths of 12", 18", 24" and 36" rolls
- 8 mil Cross Laminated Surface Film
- 5-Year Limited Warranty and Arbitration Agreement

**USES:** As an in-wall flashing membrane for use with concrete, masonry, gypsum, felt-faced and foil-faced polyisocyanurate foam insulation or wood construction.

**BUILDING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG BUILDING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY FOR MANY PRODUCTS, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.**

### LIMITATIONS

- Membrane cannot be left exposed to sunlight longer than 60 days
- Membrane must be applied when air, substrate and membrane temperatures are above 40° F
- Membrane should not be brought into contact with products containing coal-tar pitch
- Not intended for use on roofs or prolonged exposure to temperatures above 200° F
- Use only outdoors or in a well-ventilated area

### TYPICAL PHYSICAL PROPERTIES

| Roll Widths <sup>†</sup>       | Roll Size   | Coverage per Ctn. | Rolls per Ctn. |
|--------------------------------|---|-------------------|----------------|
| 12"                            | 12" × 75'   | 225 sq. ft.       | 3              |
| 18"                            | 18" × 75'   | 225 sq. ft.       | 2              |
| 24"                            | 24" × 75'   | 150 sq. ft.       | 1              |
| 36"                            | 36" × 75'   | 225 sq. ft.       | 1              |
| Film Surfacing                 | 8 mil Cross Laminated<br>High Density Polyethylene Film |                   |                |
| Asphalt Modifier               | Styrenic Block Copolymer                                |                   |                |
| Product Thickness <sup>†</sup> | 40 mil  |                   |                |

<sup>†</sup>Subject to manufacturing variation



**IMPORTANT SAFETY INFORMATION:** Do not install until all appropriate safety precautions have been read and understood. The TAMKO Safety Data Sheet (SDS) is available at [tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

**WARNING:** Use of this product in an assembly that includes polyurethane foam insulation (including without limitation an application directly to the underside of a roof deck or within a wall assembly) may cause premature degradation or failure of this product. We are investigating compatibility of polyurethane foams with our asphalt building products. Chemical incompatibility, off-gassing after application and excess heat during and after application of polyurethane foams may affect the performance of asphalt and modified asphalt building products and metal fasteners used with those products.

**WARNING:** This product contains crystalline silica. Crystalline silica have been classified as "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product contains asphalt. The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

**TAMKO**®  
BUILDING PRODUCTS LLC

P.O. Box 97  
Galena, KS 66739-0097  
800-641-4691  
[tamko.com](http://tamko.com)